


- Specification:
1. 100% OPEN SHORT AND MISS WIRE TESTS.
 2. Insulation Resistance: DC300V, $R \geq 10M\Omega$
 3. Contact Resistance: 2Ω MAX

A/M	MINI 5P
R1US004M11	R2MKU003M01

PIN ASSIGNMENT:

P1	COLOR	P2	AWG
1	RED	1	24#
2	WHITE	2	28#
3	GREEN	3	28#
4	BLACK	5	24#
	SHIELD	SHIELD	



5	OVERMOLD	12G	A0P45G01*	PVC 45Pa	COLOR: CLEAR
4	INNERMOLD	1.5G	A0005G01*	PE LOW DENSITY	
3	CONN	1PCS	3D50SP-30N-1*	MINI USB 5P B/M G/F (MOLDING TYPE) C:BLACK	
2	CONN	1PCS	3DAS04P-40N-W1*	USB A TYPE MALE G/F (SOLDER TYPE) C:WHITE	
1	CABLE	0.6M	ECA05G0104803*	UL 2725 700127*1P-70020T*2C-AL-70016T+1644010T 0D:4.8 C3透明色	
NO.	DESCRIPTION	QTY.	PART NO.	MATERIAL	
GENERAL TOLERANCE		ANGLE TOLERANCE			
X.	±0.5	X.	±2.0°		
.X	±0.05	X.	±1.0°		
.XX	±0.01	.XX	±0.5°		
.XXX	±0.005				
材 料:					
规格要求:					
比 例: 1:1	单 位: mm				
角 法:					

USB 2.0 A Male to B Mini 5 Pin Cable

品 名: USB A 公 TO MINI 5P 透明线
模具编号:

姓 名: 刘玉泽

日 期: 2008-08-18

审 核:

核 准:

数 量:

版 本:

模 具 编 号: